HUSTLER





1652601 :Clear Lens



1652602 : Smoke Lens



1652607: Grey/Green Polarised Lens



32 g

- **HIGH GLOSS, NYLON FRAME**
- **+** RUBBER NOSE PAD FOR NON-SLIP FIT
- **+** EVA TEMPLE TIPS FOR SUPERIOR COMFORT
- **+** 8 BASE CURVE



HUSTLER

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
HUSTLER	Clear	1652601	Ю	AS/NZS 1337.2010	Anti-scratch/Anti-fog
	Smoke	1652602	13	AS/NZS 1337.2010	Anti-scratch/Anti-fog
	Grey/Green Polarised	1652607	13	AS/NZS 1337.2010	Hardcoat

LENS MARKING

- 1. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 3. Range of luminous transmittance 8 -18% (smoke & polarised).

APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory

MAIN MARKETS

- Transport
- Mining
- Construction
- Local government and councils Utilities: power, gas and water
- Manufacturing

LENSES

- 2mm polycarbonate
- 8 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of lenses: Clear and Smoke
- 100% UV 385 Clear
- 100% UV 400 Smoke and Polarised

CLEANING AND STORAGE

CLEANING: Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS				
LENSES	PC - 2,2 mm - Curve 8			
FRAME	High gloss Nylon			
TEMPLES	PC + TPR			
STRAP	Non Applicable			
FOAM	Non Applicable			
SPARE LENSES	No			

FRAME MARKING

AS/NZS 1337.1.2010: Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd 32-40 Fairchild Street Heatherton VIC 3202 T: 1300 138 098 E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited Unit 5, 114 Sawyers Arms Road Papanui, Christchurch 8052 T: 03 3751400 E: bolle@bolle.co.nz

